

5 MEGA IP DOME CAMERA


EDWYUC-HL88



Feature

- 5 Mega pixel high resolution
- H.264/MPEG-4/M-JPEG triple streams codec
- Up to 32G SD card recording for alarm trigger & network outage
- ICR built in / Day&Night Switch time control
- 2-way audio
- Mobile view support
- Digital Wide Dynamic Range / Shutter Speed adjustment
- PoE Support

Server	Compression	Triple streams : H.264/MPEG-4/JPEG
	Pixel (H x V)	2592x1944 / 2048x1536 / 1920x1080 / 1280x720 / 640x480 / 320x240 / 176x144
	Traffic Control	32/48/64/96/128/192/256/320/384/448/512/576/640/704/768Kbps
	Max. Frame Rate	1/1.5/2/2.5/3/3.5/4/5/6/7/8/9/10Mbps (15fps)2592x1944, (20fps)2048x1536 (30fps)1920x1080 / 1280x720 / 640x480 / 320x240 / 176x144
	Safety	User-ID and password
	Protocols	Ipv4/v6 / HTTP / HTTPS / QoS Layer 3 level / FTP / SMTP / Bonjour / UPnP / SNMPv1/v2c/v3 DNS / DDNS / NTP / RTSP / RTP / UDP / IEEE 802.1x / DHCP / Access list filetering
	Number of User	Max. 10 connections for singal video
	Storage Capacity	SD card / FTP / NAS(Samba)
	Alerting	SMTP / FTP / HTTP / SD
	Pre / Post Alarm	Pre (0,1,2,3,4,5)/ Post (0,1,2,3,4,5,10) seconds
Release for alarm	Motion detection/ I/O / schedule	
Network Camera	Image Sensor	1/3.2" 5 Megapixel CMOS sensor
	D-WDR	Off (1~8 level)
	Shutter Time	outdoor / indoor/ (1/30, 1/50, 1/60, 1/100, 1/125, 1/250, 1/500, 1/1000)
	Video Output	BNC (1Vp-p, 75 Ohms)
	Min Illum	1.5 Lux(color) / 1.0 Lux(B/W)
	Optical Lens	3 ~ 9mm / F1.8
	IR LED / Range	18pcs / 15M
	Day / Night	Light Senso Mode / Color Mode(Day) / B/W Mode(Night) / Times Mode / Synchronize with DI input
Audio	Audio	2-way-halfduplex
	Audio Compression	G.711(64Kbps) / G.726(24Kbps) / G.726(32Kbps)
	Adjust Volume	Mic-in / Line-out web adjustable
	Audio In	Interior Line-in
	Audio Out	Interior Line-out
Terminal	Network Interface	Ethernet (10Base-T/100Base-Tx) / PoE
	Video Interface	BNC, Video composit (NTSC/PAL)
	External Port	DI / DO
	SD Card	SD Card (up tp 32GB)
General	Operation Voltage	12V DC : max. 5.52W PoE(802.3af above) : max. 6.72W
	Dimen./Weight	132mm (φ)x 108.4mm(H) / @ 680g / 16pcs per carton
	Operation Temp.	-10 ~ +45



YUK D07 L-Type bracket (option)

Certificate : CE , FCC , RoHS

*No SD card slot & local storage function for Argentina